

Gimbal

Zhiyun Weebill-2 3-Axis Combo Kit with Sling Grip Handle and Fabric Carry Case

Screen size and type: 5.5-inch FHD touch screen

Resolution: 1920 x 1080

Pixel density: 400PPI

Contrast ratio: 1200:1

Peak brightness: 1000nit

Battery: Operation voltage

Max: 12.6V

Standard: 11.1V

Min: 9.8V (Lab Data)

Operation current

Max: 6000mA

Min: 160mA

Operation temperature

Max: 45-degree

Standard: 25-degree

Min: -10-degree

Battery runtime:

Standard: 9h (The WEEBILL-2 is fully charged with a 18650-2600mAh battery)

Output voltage:

Standard: 5V

Charging time

Standard: 1.6h (This test is conducted with a 24W PD Fast Charge at a specified temperature of 25-degree . The charging time is 1.6h)

Stabilizer:

Following deviation in motion state:

Max: ± 0.3 -degree

Standard: ± 0.1 -degree

Min: ± 0.05 -degree

Following deviation in static state:

Max: ± 0.04 -degree

Min: ± 0.01 -degree

Tilt mechanical range:

Max: +190-degree

Min: -150-degree

Roll mechanical range:

Max: +80-degree

Min: -260-degree

Pan mechanical range:

Standard: 360-degree

Product Size: 319 x 225 x 62 (W*D*H)

Product net weight (Individual device): 1.47KG (including battery)

Compatible Cameras:

Sony A9 II, A9, A7R4, A7R3, A7M3, A7S3, A7R2, A7M2, A7S2, A7C, A6600, A6500, A6400, A6300, A6100

Canon 5D3, 5D4, 5DS, 5DS R, 6D, 6D2, 80D, 90D, M50, EOS R5, EOS M6 Mark 2, EOS R6, EOS R, EOS RP

Nikon D850, D780, Z5, Z6, Z7, Z6 II, Z7 II, Z50

Panasonic G9, GH5, GH5S, S1, S1H, S5, DC-BGH1

FUJIFILMX-T3, X-T4, X-T30Z CAM

ZCAM E2, Blackmagic BMPCC 4K, BMPCC 6K

Sigma SIGMA FP, Olympus OM-D E-M1 Mark II